



# Graviton



# Graviton



## Graviton Product Specifications

**Material:** The center pole is constructed of 5" OD steel round tube (11 ga.). Tube is 1010 hot rolled, Flo-Coat, galvanized pipe manufactured from steel, cold formed and high frequency induction welded continuously. It conforms to ASTM A-135 and ASTM A-500 and is tested in accordance with ASTM-8. The top of 5" steel tube contains (2) sealed bearings. The bottom circular hand rail is 1.25" galvanized steel tube (11 ga.). The top circular rail is 2" galvanized steel tube (11ga.). The top and bottom rails are supported by .25" perforated steel (14 ga.), which has .50" solid steel spacer rods welded to the top and bottom rails. There are (8) ropes constructed of UV stabilized 16mm steel-reinforced rope. The rope has a synthetic covering. Ropes are attached to the 5" steel tube and top circular rails with cast-aluminum end fittings. The cast-aluminum end fittings are attached to .50" steel tabs welded to the top circular rail.

The entire product is powder coated. All our Powder Coating products meet AAMA 2603 standards of high performance coatings. Following our Chemical cleaning process of our metals we start with a Three (3) coat application in our powder coating operations: Applying Advanced Technology in Powder Primers and Top Coats to Maximize Corrosion Protection for exterior environments.

Use Zone: 17' Diameter

Size: 60" x 60" x 88"

Fall Height: 76"

Weight of the Product: 175 lbs.

Capacity: 5 children, ages 5-12

Xccent Play! - [www.xccentplay.com](http://www.xccentplay.com)  
100 Industrial Drive  
Osceola, WI 54020  
(800) 933-4748 (715) 294-2236

